




JLS07UGD5-3

1-Line Uni-directional High Power TVS Diode

Description


The JLS07UGD5-3 is a high power TVS, utilizing leading monolithic silicon technology to provide fast response time and low ESD clamping voltage, making this device an ideal solution for protecting voltage sensitive lines.. It is assembled into a 3-pin DFN2020-3 lead-free package. The leads are finished with NiPdAu. Each device will protect one line. The combination of small size, and high surge capability makes them ideal for use in applications such as cellular phones, LCD displays, USB, and multi media card interfaces.

Circuit Diagram



Transparent bottom view

Marking Diagram



Transparent top view

73P:Device Marking Code

Bar denotes cathode

Features

- * 5500W peak pulse power (8/20μs)
- * Low leakage: nA level
- * Operating voltage: 7V
- * Ultra low clamping voltage
- * One power line protects
- * Complies with following standards:
 - IEC 61000-4-2 (ESD) immunity test
 - Air discharge: ±30kV
 - Contact discharge: ±30kV
 - IEC61000-4-5 (Lightning) 250A (8/20μs)
- * RoHS Compliant
- * Package: DFN2020-3
- * Lead Finish: NiPdAu

Applications

- * Power Management
- * Industrial Application
- * Power Supply Protection
- * Many other portable devices

Ordering Information

Part Number	Packaging	Reel Size
JLS07UGD5-3	3000/Tape & Reel	7 inch



JLS07UGD5-3

Absolute Maximum Ratings ($T_A=25^\circ\text{C}$ unless otherwise specified)


Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20 μs)	Ppk	5500	W
Peak Pulse Current (8/20 μs)	IPP	250	A
ESD per IEC 61000-4-2 (Air)	VESD	± 30	kV
ESD per IEC 61000-4-2 (Contact)		± 30	
Operating Temperature Range	TJ	-55 to +125	$^\circ\text{C}$
Storage Temperature Range	Tstg	-55 to +150	$^\circ\text{C}$

Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Reverse Working Voltage	V_{RWM}				7	V
Breakdown Voltage	V_{BR}	$I_T = 1\text{mA}$	7.5			V
Reverse Leakage Current	I_R	$V_{RWM} = 7\text{V}$			1.0	μA
Clamping Voltage	V_C	$I_{PP} = 150\text{A}$ (8 x 20 μs pulse)		16.0		V
Clamping Voltage	V_C	$I_{PP} = 250\text{A}$ (8 x 20 μs pulse)		23.0		V
Junction Capacitance	C_J	$V_R = 0\text{V}$, $f = 1\text{MHz}$		650		pF

Portion Electronics Parameter


Symbol	Parameter
I_T	Test Current
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_C
I_F	Forward Current
V_F	Forward Voltage @ I_F






JLS07UGD5-3


Typical Performance Characteristics ($T_A=25^\circ\text{C}$ unless otherwise Specified)




Junction Capacitance vs. Reverse Voltage




Clamping Voltage vs. Peak Pulse Current




Peak Pulse Power vs. Pulse Time



IEC61000-4-2 Pulse Waveform




Power Derating Curve




8 X 20us Pulse Waveform



DFN2020-3 Package Outline Drawing



Suggested Land Pattern



NOTICE

Jelan-Link reserves the right to make changes without further notice to any products here in.

Only obligations are those in the Jelan-Link Standard Terms and Conditions of Sale and in no case will Jelan-Link be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of its products.